

Serial Number: 10/662,066
In reply to Office Action dated 09-09-05
Page 2 of 15

Amendments to the Specification

Please amend the specification as follows.

Page 7, paragraph 0024 is amended as follows:

[0024] Figs. 1, 10 and 11 are is a sectional side elevation views of a preferred embodiment and two alternative embodiments of the spray nozzle of the present invention, respectively, each having different methods of attaching the flexible spray tip to the nozzle body;

Page 14, paragraph 0050 is added as follows:

[0050] While the nozzle 10 of the present invention has been described in considerable detail, Figs. 10 and 11 depict two alternative embodiments. Fig. 10 illustrates nozzle 210 which is substantially similar to the previously described nozzle, however, simply has flexible spray tip 20 molded into nozzle body 240. Similarly, Fig. 11 illustrates nozzle 310, which utilizes a slightly different attachment methodology. Specifically, flexible spray tip 20 is simply welded to nozzle body 340 forming a fluid tight seal there between.

Page 14, previous paragraph now number 0060

[0060] The invention has herein been described in its preferred embodiments to provide those skilled in the art with the information needed to apply the novel principles and to construct and use the embodiments of the examples as required. However, it is to be understood that the invention can be carried out by specifically different devices and that various modifications can be accomplished without departing from the scope of the invention itself, which is set out in the following claims: